

GEATER HYDERABAD MUNICIPAL CORPORATION

Office of the Executive Engineer
Cir -15Engg-Div-15 ,GHMC
7TH Floor, Abids Parking Complex,
Abids, Hyderabad.

Lr. No. EE/Cir-15/ Engg Div-15/SBZ/GHMC-2024-25

Date: 29-11-2024


To
The Commissioner Information & Public Relation Dept.
Greater Hyderabad Municipal Corporation,
A.C.Guards,
Hyderabad.

Sub: NIT:No. 39/Cir-15/Engg-Div-15/SBZ/GHMC/2024-25 dt: 29-11-2024.

Name of the work: Quotations invited for Maintenance of water plant at Indira Park in Circle - 15, Secunderabad Zone, GHMC in three languages and furnish the paper cutting to this office for record. Further details can be seen at website:<https://ghmc.gov.in>.

Yours faithfully,

Executive Engineer
Div No.15, GHMC.


29/11/24


GREATER HYDERABAD MUNICIPAL CORPORATION
NIT No. 39/EE/Divn.15/SBZ/GHMC/2024-25 dated 29-11-2024

S.No.	Quotation are invited from Manufactures, Fabricators, Authorities and Dealers . Agencies etc., for the below mentioned items.	Bid Document Download, Start Date & Time / Bid Submission closing date & Time	Name & Address Office & Cell No.
1	<p>Ascending Descending Waves Fountain: 1 Supply and installation of Swing Nozzles - 3/4 Brass made Nozzle coated with chromium plating, BSP Thread moving, O ring, Water output nose- 4 mm. BFF 900 306 275400 2 Supply and installation of Pump 7.5 Hp 3 phase 2900 rpm Horizontal open well submersible pump set Make- CRI/Kirloskar 43470 2 86940 3 Supply and installation of Fountain Grit Stainless Steel 304 grade Fabrication, Drilling, threading, buffing, metal Soap Cleaning, Holding Angle Clamp etc 70000 2 140000 4 Panel box :- Electrical Panel: is to be fixed inside all weather proof outdoor enclosure made of sheet steel with powder coated painted all the components of control panel should be reputed make like Delta Starter (LT & LK). Incoming outgoing terminal box – 1No. 4 Pole 32 Amps MCCB – 1 No. Voltmeter S/S – 1 No. Ammeter with S/S-1 No. Indicator Lamps – 3 Nos. On/off Switch – 1 No. On/Off Indication Lamps – (1 Set) BFF 25000 2 50000 5 Supply and installation of Under water LED lighting: Supply and fixing of LED lighting:- RGB220V/25Watt Supply:ACV-240v 50/60Hz Lamp:25w x 9pcs Spec 3Watt high brightness LED (Red/Green/Blue) BFF-UW/25W Body stainless steel Grade 316 Size Outer dia 180mm Height 75mm dia Double Ring Inner dia 115 mm Highly Quality gasket 5mm thick Toughen Glass nut/bolts output power 27w luminous flux output 80/90/100 LM/W 120° Lens Light Source High power/Edison/Cree Grade-IP68 LED Auto color change/DMX512 Controllable BFF 12500 80 1000000 6 Supply and installation of Cable- 1.5 sq. mm cable for Lights (ISI/ISO) Rubber Insulation 75 250 18750 7 Supply and installation of 2.5 sq. mm Submersible3 core cable for pump set (ISI/ISO) 104 200 20800 9 Supply and installation of Stainless Steel Mesh Box 304 Grade for the protection of Nozzles, Submersible openwell pumpset inlet suction</p>	<p>30-11-2024 12.00 PM</p> <p>04-12-2024 12.00 PM</p>	<p>Sealed quotations can be submitted in the O/o Executive Engineer–Divn- 15, GHMC, Parking Complex, 7th Floor, Abids, Hyd.</p> <p>Cell : 9704456422</p> <p>Cell : 7337557241</p> <p>on or before dt: 04-12-2024 12.00 P.M</p>
2	<p>Peacock Jet Fountain Right/Lift : Supply and installation of Swing Nozzles - 3/4 Brass made Nozzle coated with chromium plating, BSP Thread moving, O ring, Water output nose- 4 mm. 2) Supply and installation of Pump 7.5 Hp 3 phase 2900 rpm Horizontal open well submersible pump set Make- CRI/Kirloskar 3cification Description Make Rate Qut Amount 1 Design / Application Data: Small tapered Adjustable clear stream nozzle develops display with a minimum of distortion. Designed for precision use with spray ring, spray bars or other installations where precision vertical columns or trajectory patterns are desired.3/8 Brass Nozzle with Chromium Plated 4mm Bore Socket One Side BSP Thread Other Side BSW Thread Coupler BSP 15mm Height, 20mm Dia, Ejector Height 45mm, Rubber O-Ring, 60° To 90° Movement BFF 900 96 86400 3teer-19 Nozzle:- 32mm BSW-11 Input Water Volume 25mm Bore Height 115mm Nozzle Dia 130mm Nozzle height 100mm Aluminum Alloy Powder Coated Output Water Volume 4mm 19 Jets With Inbuilt 3/8 Water Controllers BFF 10200 6 61200 Fountain Grit –2"dia GI Pipe Banding Fabrication Flange In Let 3/8 MS Coupling Drilling and Lighting Clamping 6' Grit BFF 35000 2 70000 2 Supply and installation of Pump 7.5 Hp 3 phase 2900 rpm Horizontal open well submersible pump set Make- CRI/Kirloskar 43470 2 86940 3 Supply and installation of 3Tier with Peacock Jet Fountain Grit Stainless Steel 304 grade Fabrication, Drilling, threading, buffing, metal Soap Cleaning, Holding Angle Clamp etc 4) Panel box :- Electrical Panel: is to be fixed inside all weather proof outdoor enclosure made of sheet steel with powder coated painted all the components of control panel should be reputed make like Delta Starter (LT & LK). Incoming outgoing terminal box – 1No. 18 to 24 Relay capacity 4 Pole 32 Amps MCB – 1 No. Voltmeter S/S – 1 No. Ammeter with S/S-1 No. Indicator Lamps – 3 Nos. On/off Switch – 1 No. On/Off Indication Lamps – 4 Nos. (1 Set) 5) Supply and installation of Under water LED lighting: Supply and fixing of LED lighting:- RGB 220V/25Watt Supply:ACV- 240v 50/60Hz Lamp:25w x 9pcs Spec 3Watt high brightness LED (Red/Green/Blue) BFF-UW/25W Body stainless steel Grade 316 Size Outer dia 180mm Height 75mm dia Double Ring Inner dia 115 mm Highly Quality gasket 5mm thick Toughen Glass nut/bolts output power 27w luminous flux output 80/90/100 LM/W 120° Lens Light Source High power/Edison/Cree Grade-IP68 LED Auto color change/DMX512 Controllable 6) Supply and installation of Cable- 1.5 sq. mm cable for Lights (ISI/ISO) Rubber Insulation 7) Supply and installation of 2.5 sq. mm Submersible3 core cable for pump set (ISI/ISO) 9) Supply and installation of Stainless Steel 8" x8"x12" Mesh Box 304 Grade for the protection of Nozzles, Submersible open well pump set inlet suction.</p>		

3	<p>Finger Peacock Tail Fountain : 1) Design / Application Data: Small tapered Adjustable clear stream nozzle develops display with a minimum of distortion. Designed for precision use with spray ring, spray bars or other installations where precision vertical columns or trajectory patterns are desired. 3/8 Brass Nozzle with Chromium Plated 4mm Bore Socket One Side BSP Thread Other Side BSW Thread Coupler BSP 15mm Height, 20mm Dia, Ejector Height 45mm, Rubber O-Ring, 60° To 90° Movement 3teer-19 Nozzle:- 32mm BSW-11 Input Water Volume 25mm Bore Height 115mm Nozzle Dia 130mm Nozzle height 100mm Aluminum Alloy Powder Coated Output Water Volume 4mm 19 Jets With Inbuilt 3/8 Water Controllers Fountain Grit 2"dia GI Pipe Banding Fabrication Flange In Let 3/8 MS Coupling Drilling and Lighting Clamping 6' Grit 2) Supply and installation of Pump 7.5 Hp 3 phase 2900 rpm Horizontal open well submersible pump set Make- CRI/Kirloskar 43470 2 86940 3 Supply and installation of 3Tier with Peacock Jet Fountain Grit Stainless Steel 304 grade Fabrication, Drilling, threading, buffing, metal Soap Cleaning, Holding Angle Clamp etc 4) Panel box :- Electrical Panel: is to be fixed inside all weather proof outdoor enclosure made of sheet steel with powder coated painted all the components of control panel should be reputed make like Delta Starter (LT & LK). Incoming outgoing terminal box – 1No. 18 to 24 Relay capacity 4 Pole 32 Amps MCB – 1 No. Voltmeter S/S – 1 No. Ammeter with S/S-1 No. Indicator Lamps – 3 Nos. On/off Switch – 1 No. On/Off Indication Lamps – 4 Nos. (1 Set) 5) Supply and installation of Under water LED lighting: Supply and fixing of LED lighting:- RGB 220V/25Watt Supply: ACV- 240v 50/60Hz Lamp: 25w x 9pcs Spec 3Watt high brightness LED (Red/Green/Blue) BFF-UW/25W Body stainless steel Grade 316 Size Outer dia 180mm Height 75mm dia Double Ring Inner dia 115 mm Highly Quality gasket 5mm thick Toughen Glass nut/bolts output power 27w luminous flux output 80/90/100 LM/W 120° Lens Light Source High power/Edison/Cree Grade-IP68 LED Auto color change/DMX512 Controllable 6) Supply and installation of Cable- 1.5 sq. mm cable for Lights (ISI/ISO) Rubber Insulation 7) Supply and installation of 2.5 sq. mm Submersible 3 core cable for pump set (ISI/ISO) 9) Supply and installation of Stainless Steel 8" x8"x12" Mesh Box 304 Grade for the protection of Nozzles, Submersible open well pump set inlet suction</p>		
---	--	--	--

Further details and complete specification for the above items can be obtained from GHMC website: <https://ghmc.gov.in/>

To,
The Notice Board


EXECUTIVE ENGINEER
 Division No. 15, GHMC


 29/11/24


GREATER HYDERABAD MUNICIPAL CORPORATION

Office of the Executive Engineer
Cir -15Engg-Div-15 ,GHMC
7TH Floor, Abids Parking Complex,
Abids, Hyderabad.

QUOTATIONS

- 1) **Ascending Descending Waves Fountain:** 1 Supply and installation of Swing Nozzles - 3/4 Brass made Nozzle coated with chromium plating, BSP Thread moving, O ring, Water output nose- 4 mm. BFF 900 306 275400 2 Supply and installation of Pump 7.5 Hp 3 phase 2900 rpm Horizontal open well submersible pump set Make- CRI/Kirloskar 43470 2 86940 3 Supply and installation of Fountain Grit Stainless Steel 304 grade Fabrication, Drilling, threading, buffing, metal Soap Cleaning, Holding Angle Clamp etc 70000 2 140000 4 Panel box :- Electrical Panel: is to be fixed inside all weather proof outdoor enclosure made of sheet steel with powder coated painted all the components of control panel should be reputed make like Delta Starter (LT & LK). Incoming outgoing terminal box – 1No. 4 Pole 32 Amps MCCB – 1 No. Voltmeter S/S – 1 No. Ammeter with S/S-1 No. Indicator Lamps – 3 Nos. On/off Switch – 1 No. On/Off Indication Lamps – (1 Set) BFF 25000 2 50000 5 Supply and installation of Under water LED lighting: Supply and fixing of LED lighting:- RGB220V/25Watt Supply:ACV-240v 50/60Hz Lamp:25w x 9pcs Spec 3Watt high brightness LED (Red/Green/Blue) BFF-UW/25W Body stainless steel Grade 316 Size Outer dia 180mm Height 75mm dia Double Ring Inner dia 115 mm Highly Quality gasket 5mm thick Toughen Glass nut/bolts output power 27w luminous flux output 80/90/100 LM/W 120° Lens Light Source High power/Edison/Cree Grade-IP68 LED Auto color change/DMX512 Controllable BFF 12500 80 1000000 6 Supply and installation of Cable- 1.5 sq. mm cable for Lights (ISI/ISO) Rubber Insulation 75 250 18750 7 Supply and installation of 2.5 sq. mm Submersible3 core cable for pump set (ISI/ISO) 104 200 20800 9 Supply and installation of Stainless Steel Mesh Box 304 Grade for the protection of Nozzles, Submersible openwell pumpset inlet suction
- 21 **Peacock Jet Fountain** Right/Lift : Supply and installation of Swing Nozzles - 3/4 Brass made Nozzle coated with chromium plating, BSP Thread moving, O ring, Water output nose- 4 mm. 2) Supply and installation of Pump 7.5 Hp 3 phase 2900 rpm Horizontal open well submersible pump set Make- CRI/Kirloskar 3cification Description Make Rate Qut Amount 1 Design / Application Data: Small tapered Adjustable clear stream nozzle develops display with a minimum of distortion. Designed for precision use with spray ring, spray bars or other installations where precision vertical columns or trajectory patterns are desired.3/8 Brass Nozzle with Chromium Plated 4mm Bore Socket One Side BSP Thread Other Side BSW Thread Coupler BSP 15mm Height, 20mm Dia, Ejector Height 45mm, Rubber O-Ring, 60° To 90° Movement BFF 900 96 86400 3teer-19 Nozzle:- 32mm BSW-11 Input Water Volume 25mm Bore Height 115mm Nozzle Dia 130mm Nozzle height 100mm Aluminum Alloy Powder Coated Output Water Volume 4mm 19 Jets With Inbuilt 3/8 Water Controllers BFF 10200 6 61200 Fountain Grit -2"dia GI Pipe Banding Fabrication Flange In Let 3/8 MS Coupling Drilling and Lighting Clamping 6' Grit BFF 35000 2 70000 2 Supply and installation of Pump 7.5 Hp 3 phase 2900 rpm Horizontal open well submersible pump set Make- CRI/Kirloskar 43470 2 86940 3 Supply and installation of 3Tier with Peacock Jet Fountain Grit Stainless Steel 304 grade Fabrication, Drilling, threading, buffing, metal Soap Cleaning, Holding Angle Clamp etc 4) Panel box :- Electrical Panel: is to be fixed inside all weather proof outdoor enclosure made of sheet steel with powder coated painted all the components of control panel should be reputed make like Delta Starter (LT & LK). Incoming outgoing terminal box – 1No. 18 to 24 Relay capacity 4 Pole 32 Amps MCB – 1 No. Voltmeter S/S – 1 No. Ammeter with S/S-1 No. Indicator Lamps – 3 Nos. On/off Switch – 1 No. On/Off Indication Lamps – 4 Nos. (1 Set) 5) Supply and installation of Under water LED lighting: Supply and fixing of LED lighting:- RGB 220V/25Watt Supply:ACV- 240v 50/60Hz Lamp:25w x 9pcs Spec 3Watt high brightness LED (Red/Green/Blue) BFF-UW/25W Body stainless steel Grade 316 Size Outer dia 180mm Height 75mm dia Double Ring Inner dia 115 mm Highly Quality gasket 5mm thick Toughen Glass nut/bolts output power 27w luminous flux output 80/90/100 LM/W 120° Lens Light Source High power/Edison/Cree Grade-IP68 LED Auto color change/DMX512 Controllable 6) Supply and installation of Cable- 1.5 sq. mm cable for Lights (ISI/ISO) Rubber Insulation 7) Supply and installation of 2.5 sq. mm Submersible3 core cable for pump set (ISI/ISO) 9) Supply and installation of Stainless Steel 8" x8"x12" Mesh Box 304 Grade for the protection of Nozzles, Submersible open well pump set inlet suction.

3) **Finger Peacock Tail Fountain** : 1) Design / Application Data: Small tapered Adjustable clear stream nozzle develops display with a minimum of distortion. Designed for precision use with spray ring, spray bars or other installations where precision vertical columns or trajectory patterns are desired. 3/8 Brass Nozzle with Chromium Plated 4mm Bore Socket One Side BSP Thread Other Side BSW Thread Coupler BSP 15mm Height, 20mm Dia, Ejector Height 45mm, Rubber O-Ring, 60° To 90° Movement 3teer-19 Nozzle:- 32mm BSW-11 Input Water Volume 25mm Bore Height 115mm Nozzle Dia 130mm Nozzle height 100mm Aluminum Alloy Powder Coated Output Water Volume 4mm 19 Jets With Inbuilt 3/8 Water Controllers Fountain Grit 2"dia GI Pipe Banding Fabrication Flange In Let 3/8 MS Coupling Drilling and Lighting Clamping 6' Grit 2) Supply and installation of Pump 7.5 Hp 3 phase 2900 rpm Horizontal open well submersible pump set Make- CRI/Kirloskar 43470 2 86940 3 Supply and installation of 3Tier with Peacock Jet Fountain Grit Stainless Steel 304 grade Fabrication, Drilling, threading, buffing, metal Soap Cleaning, Holding Angle Clamp etc 4) Panel box :- Electrical Panel: is to be fixed inside all weather proof outdoor enclosure made of sheet steel with powder coated painted all the components of control panel should be reputed make like Delta Starter (LT & LK). Incoming outgoing terminal box – 1No. 18 to 24 Relay capacity 4 Pole 32 Amps MCB – 1 No. Voltmeter S/S – 1 No. Ammeter with S/S-1 No. Indicator Lamps – 3 Nos. On/off Switch – 1 No. On/Off Indication Lamps – 4 Nos. (1 Set) 5) Supply and installation of Under water LED lighting: Supply and fixing of LED lighting:- RGB 220V/25Watt Supply:ACV- 240v 50/60Hz Lamp:25w x 9pcs Spec 3Watt high brightness LED (Red/Green/Blue) BFF-UW/25W Body stainless steel Grade 316 Size Outer dia 180mm Height 75mm dia Double Ring Inner dia 115 mm Highly Quality gasket 5mm thick Toughen Glass nut/bolts output power 27w luminous flux output 80/90/100 LM/W 120° Lens Light Source High power/Edison/Cree Grade-IP68 LED Auto color change/DMX512 Controllable 6) Supply and installation of Cable- 1.5 sq. mm cable for Lights (ISI/ISO) Rubber Insulation 7) Supply and installation of 2.5 sq. mm Submersible 3 core cable for pump set (ISI/ISO) 9) Supply and installation of Stainless Steel 8" x8"x12" Mesh Box 304 Grade for the protection of Nozzles, Submersible open well pump set inlet suction


EXECUTIVE ENGINEER
Division No. 15, GHMC

29/11/24